



# Product Guide

## POLYSTYRENE IS ONE OF THE MOST USEFUL SHEET MATERIALS. IT LOOKS GOOD WHILST GIVING TRUE VALUE FOR MONEY.

Polycasa PS can be easily cut to size, allowing for a wide range of finished picture-frames to be produced from standard stock sheet. If you need to produce a cheap but effective sign for a short campaign, this sheet material is the perfect choice.

And you can easily achieve the very latest style in sanitary ware by choosing one of the wide range of textured finishes. Whatever the application, PS is the versatile material that delivers sparkling clarity, with light weight and good resistance to breakage.

### PRODUCT IDENTIFICATION

PS is the brand name for Polycasa's extruded Crystal Polystyrene sheets, offering solutions for many indoor applications.

As well clear, anti-reflex and standard opal white, a variety of colours and designs are also available as a result of the extrusion process Polycasa can offer.

### CHARACTERISTICS

- Good optical properties and a brilliant surface.
- High light transmission (min 88% wavelength: 500 nm, thickness 3 mm).
- Low price.
- Low density (1.05).
- Good chemical resistance and high rigidity.
- UV-stabilised — remains colour constant for many years when used indoors. (On special request Polycasa PS sheets can be produced without UV-stabilisation. They then meet all current food contact legislation and can be used in contact with foodstuffs.)
- Possibility of corona treatment - process to increase surface tension. (The result after corona treatment is a surface that is unchanged to the naked eye, but in fact is much more receptive to inks, coatings, and adhesives.)

Polycasa PS sheets also combine the following excellent properties:

- Excellent transparency.
- Good surface hardness.
- Good recyclability.
- Low water absorption.

### APPLICATIONS

- Picture frames.
- Shower cabin doors (flat and curved).
- Indoor glazing.



### PRODUCT RANGE

- Available as a flat, patterned or prismatic sheet.
- The range of patterns is extensive (subject to special conditions).
- Colours: clear, with or without anti-reflex features, and opal.
- Standard range of thickness is from 0.85 to 4.75 mm. (A thickness of 5mm is also available subject to special conditions.)
- Special thicknesses, colours and patterns can be produced to order, subject to conditions.

Please contact your local customer service centre for a complete product overview. For details see back of brochure.

### TECHNICAL INFORMATION

GENERAL			
Property	Method	Units	PS
Density	ISO 1183	g/cm <sup>3</sup>	1.05
Rockwell Hardness	ISO 2039-1	Mscale	150
OPTICAL			
Property	Method	Units	PS
Light Transmission	DIN 5036-3	%	89
Refractive Index	ISO 489	n <sub>D20</sub>	1.59
MECHANICAL			
Property	Method	Units	PS
Flexural Modulus	ISO 178	MPa	3450
Flexural Strength	ISO 178	MPa	85
Tensile Modulus	ISO 527-2	MPa	3400
Tensile Strength	ISO 527-2	MPa	45
Elongation	ISO 527-2	%	3
THERMAL			
Property	Method	Units	PS
Vicat Temp (VST/B 50)	ISO 306	°C	101
Heat Deflection Temp. (A)	ISO 75-2	°C	86
Specific Heat Capacity	ASTM D-2766	J/gK	1.8
Coefficient of linear thermal expansion	DIN 53752	K <sup>-1</sup> x10 <sup>-5</sup>	8
Thermal Conductivity	DIN 52612	W/mK	0.16
Degradation temperature		°C	>280
Max service temperature		°C	80
Sheet forming temp. range		°C	130-170
IMPACT STRENGTHS			
Property	Method	Units	PS
Charpy (notched)	ISO 179-1	KJ/m <sup>2</sup>	-
Charpy (unnotched)	ISO 179-1	KJ/m <sup>2</sup>	6
ELECTRICAL			
Property	Method	Units	POLYCASA PS
Volume Resistivity	DIN 53482	Ω.cm	>10 <sup>14</sup>
Surface Resistivity	DIN 53482	Ω	>10 <sup>14</sup>

Note: All mentioned data is based on extruded sheets in a thickness of 4mm

The technical data of our products are typical ones; the actually measured values are subject to production variations.

For further information on the wide range of Polycasa products please contact us as follows;

**UK and Ireland**

T: 00 44 28 67 74 11 11

**France, Italy, Greece and Cyprus**

T: 00 33 385 73 68 19

**Germany, Austria, Switzerland**

T: 00 49 61 31 63 11 82

**Spain and Portugal**

T: 00 34 93 565 12 30

**Central and Eastern Europe**

T: 00 421 41 707 14 20 – 24

**Benelux, Scandinavia and all other countries**

T: 00 32 14 57 67 11

**HEAD OFFICE**

**Polycasa**

Leukaard 1

BE 2440 Geel

Belgium

T: 00 32 14 57 67 06

F: 00 32 14 58 96 21

E: [info@polycasa.com](mailto:info@polycasa.com)

W: [www.polycasa.com](http://www.polycasa.com)

Polycasa offers an extensive range of plastic sheets to distribution and industrial partners, with an industry leading selection of polymers, thicknesses, sizes, colours, patterns, and coatings.



**Brands from Polycasa:**



While we have made every effort to ensure the accuracy of the information it is provided on an "as is" basis and without liability, particularly including (but not limited to) liability with regard to any up to date status, completeness or correctness of the information or any liability for the merchantability of products, their fitness for any particular purpose, or the infringement of third party rights. Colours of the products are for indication purposes only and may not represent the colour of the actual product. Any opinions provided in the Product Guide are not statements or representations of fact and they are not intended to form part of any offer or contract. © Polycasa Group, 2013, all rights reserved.